

# MULTI-PURPOSE

## چند منظوره

دیتا پروژکتورهای چند منظوره مکمل شامل بهترین امکانات برای کسب و کار و آموزش هستند. تمامی مدل های این سری تصویری با بالاترین حد کیفیت، امنیت و کاربری آسان ارائه می دهند. این دیتا پروژکتورها دارای قابلیت صرفه جویی در مصرف انرژی و عمر بالا هستند.



**maxell**

The above features listed may not be available on all models. Please check the specific model specification.

## MULTI-PURPOSE TECHNICAL SPECIFICATION



	MC-EW3551
<b>Description</b>	3LCD Lamp projector, 3800 ANSI lumens, 20,000:1 contrast ratio, WXGA (1280 x 800) resolution
<b>OPTICAL</b>	
<b>Panel Size</b>	3LCD 15mm (0.59")
<b>Resolution</b>	WXGA (1280 x 800)
<b>Light Output (Brightness) ANSI Lumens</b>	3800 (Normal)
<b>Contrast Ratio</b>	20,000:1
<b>Lamp Life (Hours)*</b>	6000 (Normal), 12,500 (Eco)
	Built-in
<b>Lens Zoom</b>	Manual Zoom x 1.2
<b>Lens Focus</b>	Manual Focus
<b>Throw Distance</b>	0.9 – 9.6m (Wide), 1.1 – 11.6m (Tele)
<b>Distance to Width Ratio/ Throw Ratio (:1)</b>	1.5-1.8
<b>Display Size</b>	30 - 300"
<b>FEATURES</b>	
<b>Speakers</b>	16W Mono
<b>Digital Keystone Correction</b>	Horizontal ± 30°, Vertical ± 30°
<b>CONNECTIONS</b>	
<b>Digital Input</b>	HDMI x 2 (HDCP compliant)
<b>Analogue Input</b>	15-pin Mini-D-Sub x2, RCA Jack x1
<b>Video Output</b>	15 pin Mini D-Sub x 1 (shared with analog computer input)
<b>Audio Input</b>	3.5mm Stereo Mini Jack x 2, RCA Jack (L/R) x 1
<b>Audio Output</b>	3.5mm Stereo Mini Jack x 1
<b>RS232-C Control</b>	1 x 9-pin D-Sub
<b>Wireless LAN</b>	USB-WL-5GM wireless adapter (optional)
<b>Wired LAN</b>	RJ45 connector x1
<b>USB Type-A</b>	USB Type A x1 (PC less presentation or wireless adapter)
<b>USB Type-B</b>	USB Type B x1 (USB display or USB mouse control)
<b>POWER</b>	
<b>Power Supply</b>	AC 100V – 120V / AC 220V – 240V (50/60Hz)
<b>Power Consumption Operating / Standby</b>	310W
<b>PHYSICAL</b>	
<b>Weight</b>	3.5kg
<b>Dimensions (W x H x D)</b>	349 x 264 x 88mm
<b>Noise</b>	37dB (Normal), 29dB (Eco)
<b>Filter life (Hours)</b>	10,000
<b>COMPATIBILITY</b>	
<b>Computer</b>	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/UXGA/HD (Compressed), MAC16"
<b>Video</b>	525i (480i), 525p (480p), 625i (576i), 625p (576p), 1125i (1080i@50/60), 750p (720p@50/60), 1125p (1080p@50/60)
<b>ACCESSORIES</b>	
<b>Supplied Accessories</b>	Power Cable (1.8m) x1, Computer Cable (2m) x1, IR Remote Control Unit x1, AA Batteries x2, Concise User Manual x1, Security Label x1, Lens Cover x1, Adapter Cover x1
<b>Optional Accessories</b>	USB wireless adapter USB-WL-5GM
<b>Remote Control</b>	HL03037
<b>Replacement Lamp / Filter</b>	DT02081M (without Filter) / UX39561